



# Taper-Kettenräder für Ketten nach DIN-Nr. 8187

mit gehärteten Zähnen 45–55 HRC

Zähnezahl Z	Abmessungen in mm allgemein		Artikel-Nr. Ketten Fuchs			
	de	dp	dm	A	Buchse	Typ
					321-400- (+Zähnezahl) + TLH	
					einfach	
013 TLH	87,5	79,59	63,0	25,0	1210	1
014 TLH	93,6	85,61	71,0	25,0	1610	1
015 TLH	99,8	91,63	71,0	25,0	1610	1
016 TLH	105,5	97,65	75,0	25,0	1610	1
017 TLH	111,5	103,67	76,0	25,0	1610	1
018 TLH	118,0	109,71	90,0	32,0	2012	1
019 TLH	124,2	115,75	90,0	32,0	2012	1
020 TLH	129,7	121,78	90,0	32,0	2012	1
021 TLH	136,0	127,82	102,0	45,0	2517	1
022 TLH	141,8	133,86	102,0	45,0	2517	1
023 TLH	149,9	139,90	108,0	45,0	2517	1
024 TLH	153,9	145,94	108,0	45,0	2517	1
025 TLH	160,0	152,00	108,0	45,0	2517	1
026 TLH	165,9	158,04	108,0	45,0	2517	1
027 TLH	172,3	164,09	108,0	45,0	2517	1
028 TLH	178,0	170,13	108,0	45,0	2517	1
030 TLH	190,5	182,25	108,0	45,0	2517	1

3/4" × 7/16"  
19,05 × 11,68 mm  
12B - 1



Zähnezahl Z	Abmessungen in mm allgemein		Artikel-Nr. Ketten Fuchs			
	de	dp	dm	A	Buchse	Typ
					321-510- (+Zähnezahl) + TLH	
					einfach	
013 TLH	117,0	106,12	78,0	25,0	1610	1
014 TLH	125,0	114,15	78,0	25,0	1610	1
015 TLH	133,0	122,17	78,0	25,0	1610	1
016 TLH	141,0	130,20	90,0	32,0	2012	1
017 TLH	149,0	138,22	90,0	32,0	2012	1
018 TLH	157,0	146,28	108,0	45,0	2517	1
019 TLH	165,2	154,33	108,0	45,0	2517	1
020 TLH	173,0	162,38	108,0	45,0	2517	1
021 TLH	181,2	170,43	108,0	45,0	2517	1
022 TLH	189,3	178,48	108,0	45,0	2517	1
023 TLH	197,5	186,53	108,0	45,0	2517	1
024 TLH	205,5	194,59	108,0	45,0	2517	1
025 TLH	213,5	202,66	108,0	45,0	2517	1
026 TLH	221,6	210,72	108,0	45,0	2517	1
027 TLH	229,6	218,79	108,0	45,0	2517	1
028 TLH	237,7	226,85	108,0	45,0	2517	1
030 TLH	254,0	243,00	160,0	51,0	3020	1

1" × 17,02 mm  
25,4 × 17,02 mm  
16B - 1

Zähnezahl Z	Abmessungen in mm allgemein		Artikel-Nr. Ketten Fuchs			
	de	dp	dm	A	Buchse	Typ
					321-600- (+Zähnezahl) + TLH	
					einfach	
015 TLH	167,9	152,72	108,0	45,0	2517	1
017 TLH	187,9	172,78	108,0	45,0	2517	1
019 TLH	208,1	192,91	108,0	45,0	2517	1
021 TLH	228,2	213,03	108,0	45,0	2517	1
023 TLH	248,3	233,17	108,0	45,0	2517	1
025 TLH	268,5	253,33	108,0	45,0	2517	1
030 TLH	318,9	303,75	160,0	51,0	3020	1

1 1/4" × 3/4"  
31,75 × 19,05 mm  
20B - 1