

Hakon®-Spannsätze Baureihe 110

Abmessungen / Technische Daten

Artikel-Nr. Ketten Fuchs	Abmessungen in mm							Spannschrauben		Übertragungswerte				Gewicht kg	
	Größe d×D	d ₁	D ₁	h ₁	h ₂	h ₃	H	Anzahl Stück	Größe M	M _d Nm	Dreh- moment M _t Nm	Axial- Kraft F _{ax} kN	Flächen- pressung Welle P _w N/mm ²		Nabe P _N N/mm ²
110-6077	60×77	99,0	104,0	50,0	67,0	75,0	83,0	10	M8×22	41	2969	99	84	65,0	1,600
110-6584	65×84	106,0	111,0	50,0	67,0	75,0	83,0	10	M8×22	41	3216	99	78	60,0	1,890
110-7090	70×90	113,0	119,0	60,0	80,0	91,0	101,0	10	M10×25	83	5609	160	97	76,0	2,665
110-7595	75×95	121,0	126,0	60,0	80,0	91,0	101,0	10	M10×25	83	6010	160	91	72,0	2,900
110-80100	80×100	126,0	131,0	65,0	85,0	96,0	106,0	12	M10×25	83	7693	192	94	75,0	3,200
110-85106	85×106	132,0	137,0	65,0	85,0	96,0	106,0	12	M10×25	83	8174	192	89	71,0	3,500
110-90112	90×112	138,0	143,0	65,0	85,0	96,0	106,0	15	M10×25	83	10818	240	105	84,0	3,900
110-95120	95×120	147,9	153,0	65,0	85,0	96,0	106,0	15	M10×25	83	11419	240	99	78,0	4,400
110-100125	100×125	156,2	162,0	65,0	89,0	102,0	114,0	12	M12×35	145	13999	280	102	81,0	5,400
110-110140	110×140	169,0	174,0	70,0	94,0	107,0	119,0	12	M12×35	145	15399	280	93	73,0	6,800
110-120155	120×155	188,0	198,0	90,0	115,0	128,0	140,0	12	M12×35	145	16799	280	66	51,0	9,900
110-130165	130×165	198,0	208,0	90,0	115,0	128,0	140,0	16	M12×35	145	24265	373	81	64,0	9,500