

# Abmessungen / Technische Daten

Artikel-Nr. Ketten Fuchs	Größe Mt x A	Über- tragungs- werte	Anzahl Teller- feder	Abmessungen in mm			Bohrung		Antriebs- teilstärke F max. in mm	Abmessungen in mm			Gewicht kg	Massen- trägheits- moment kg cm <sup>3</sup>
				A	B (k7)	C	D vor- gebohrt	D max. (H7)		Buchsen- länge in mm	G	H		
<b>T 650/140</b>	650 x 140	650,0	1	140,0	90,0	86,0	20,0	60,0	16,0 22,0	4,0	85,0	23,0	5,600	98,10
<b>T 1200/140</b>	1200 x 140	1200,0	2	140,0	90,0	86,0	20,0	60,0	16,0 22,0	4,0	85,0	23,0	5,600	98,10
<b>T 1000/170</b>	1000 x 170	1000,0	1	170,0	100,0	93,0	28,0	65,0	18,0 24,0	4,6	90,0	26,5	8,400	231,30
<b>T 1800/170</b>	1800 x 170	1800,0	2	170,0	100,0	93,0	28,0	65,0	18,0 24,0	4,6	90,0	26,5	8,400	231,30
<b>T 2200/200</b>	2200 x 200	2200,0	1	200,0	120,0	105,0	35,0	80,0	17,0 24,0	5,0	110,0	27,0	12,000	385,00
<b>T 4000/200</b>	4000 x 200	4000,0	2	200,0	120,0	105,0	35,0	80,0	17,0 24,0	5,0	110,0	27,0	12,000	385,00
<b>T 3800/254</b>	3800 x 254	3800,0	1	254,0	140,0	120,0	48,0	90,0	25,0 32,0	5,0	125,0	33,0	21,000	1581,00
<b>T 6800/254</b>	6800 x 254	6800,0	2	254,0	140,0	120,0	48,0	90,0	25,0 32,0	5,0	125,0	33,0	21,000	1581,00
<b>T 5500/280</b>	5500 x 280	5500,0	1	280,0	170,0	120,0	48,0	120,0	25,0 32,0	5,0	155,0	33,0	26,000	1698,00